

SAFETY DATA SHEET

5401 Impregnation Primer (Base)

1. Identification of the substance/preparation and of the company/undertaking

Product Name and/or Code : 5401 Impregnation Primer (Base)
Manufacturer : Rust-Oleum Netherlands BV, PO. Box 138, NL-4700 AC Roosendaal, The Netherlands
NV Martin Mathys, Kolenberg 23, B-3545 Zelem, Belgium
Emergency telephone number : Rust-Oleum: (+31)165-593636; Fax (+31)165-593600
Martin Mathys: (+32)13-460200; Fax (+32)13-460201
Product Use : Base for 2-component paint.

2. Composition / information on ingredients

Substance/Preparation : Preparation

Chemical name*	CAS No.	%	EC Number	Classification
Bisphenol-A-epoxy resin avg.mol.wght. < 700		50-100	500-033-5	Xi; R36/38 R43
Bisphenol-F-epoxy resin avg.mol.wght. < 700		10-25	500-006-8	N; R51/53 Xi; R36/38 R43
C12-C15 Alkylglycidylether	68609-97-2	10-25	271-846-8	N; R51/53 Xi; R36/38 R43
See Section 16 for the full text of the R Phrases declared above				

* Occupational Exposure Limit(s), if available, are listed in section 8

3. Hazards identification

The preparation is classified as dangerous according to Directive 1999/45/EC and its amendments.

The preparation may be a skin sensitizer. It also might be a skin irritant and repeated contact might increase this effect.

Classification : R36/38- Irritating to eyes and skin.
R43- May cause sensitization by skin contact.
R51/53- Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Effects and symptoms

Inhalation : Inhalation not likely under normal use conditions.
Ingestion : Harmful if swallowed. Irritating to mouth, throat and stomach.
Skin Contact : Hazardous in case of skin contact (irritant, sensitizer). Skin inflammation is characterized by itching, scaling, reddening, or, occasionally, blistering. May cause sensitization by skin contact.
Eye Contact : Hazardous in case of eye contact (irritant).
Aggravating conditions : May cause sensitization by skin contact. The onset of symptoms may be delayed. May cause allergic skin reactions with repeated exposure.

4. First-aid measures

First-Aid measures

General : In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.
Inhalation : Inhalation not likely under normal use conditions.
Ingestion : If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do not induce vomiting.
Skin Contact : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
Eye Contact : Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open.

5. Fire-fighting measures

- Extinguishing Media** : Recommended: alcohol resistant foam, CO2, powders, water spray.
Not to be used : waterjet.
- Recommendations** : Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard. Appropriate breathing apparatus may be required. Cool closed containers exposed to fire with water. Do not release runoff from fire to sewers or waterways.
- Special fire-fighting procedures** : Fire fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear.
- Hazardous thermal (de)composition products** : Thermal decomposition may release toxic and/or hazardous vapors/fumes possibly including chlorine, chloramines and nitrogen oxides (NO, NO2...)

6. Accidental release measures

- Personal precautions** : Provide adequate ventilation. Refer to protective measures listed in sections 7 and 8.
- Spill** : Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth, and place in container for disposal according to local regulations (see section 13). Do not allow to enter drains or watercourses. Clean preferably with a detergent; avoid use of solvents. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.

Note: See section 8 for personal protective equipment and section 13 for waste disposal.

7. Handling and storage

- Handling** : Keep container tightly closed. Keep away from heat, sparks and flame. No sparking tools should be used.
- Avoid contact with skin and eyes. Avoid inhalation of dust from sanding.
- Eating, drinking and smoking should be prohibited in area where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking.
- Put on appropriate personal protective equipment (see Section 8).
- Never use pressure to empty: container is not a pressure vessel. Always keep in containers made from the same material as the original one.
- Comply with the health and safety at work laws.
- Storage** : Store in accordance with local regulations. Observe label precautions. Store in a cool, well-ventilated area away from incompatible materials and ignition sources.
- Keep away from: OXIDIZING AGENTS, strong alkalis, strong acids.
No smoking. Prevent unauthorized access. Containers that are opened must be carefully resealed and kept upright to prevent leakage.
Do not empty into drains..

8. Exposure controls/personal protection

- Engineering measures** : Provide adequate ventilation. Good general ventilation should be sufficient to control airborne levels.
- Hygiene measures** : Keep away from food, drink and animal feedingstuffs. Never eat, drink or smoke in work areas. Practice good personal hygiene when using this material, especially before eating, drinking, smoking, using the toilet, or applying cosmetics. It is generally recognized that contact lenses should not be worn when working with chemicals because contact lenses may contribute to the severity of an eye injury. Persons with a history of skin sensitization problems should not be employed in any process in which this preparation is used.
- Occupational Exposure Limits** : Not available.
- Recommended monitoring procedures** : No special measures are required. General ventilation is typically sufficient. Provide eye wash and quick drench shower close to work station.
- Personal protective equipment**
- Respiratory system** : If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators.
- Skin and body** : Personnel should wear antistatic clothing made of natural fibers or of high-temperature-resistant synthetic fibers.
- Hands** : For prolonged or repeated handling, use gloves: nitrile.
- Barrier creams may help to protect the exposed areas of the skin, but should not be applied once exposure has occurred.
- Eyes** : Use safety eyewear designed to protect against splash of liquids.

9. Physical and chemical properties

Physical state	: Liquid. (Viscous / paste)
Color	: Amber.
Odor	: Practically odourless
Boiling Point	: >200°C (392°F)
Melting Point	: -10°C (14°F)
Density	: 1.1 g/cm ³ (20°C / 68°F)
Vapor Pressure	: <0.07 kPa (<0.5 mmHg) (at 20°C)
Solubility	: Partially soluble in acetone. Insoluble in cold water, hot water. Solventfree product. Do not add any thinner !
Flash point	: Closed cup: >130°C (266°F).
Fire Hazards in Presence of Various Substances	: Slightly flammable to flammable in presence of open flames, sparks and static discharge. Evolves toxic fumes when heated to the decomposition state.
Autoignition temperature	: >400°C (752°F)
Explosive properties	: Risks of explosion of the product in presence of mechanical impact: Not available. Risks of explosion of the product in presence of static discharge: Not available.
Viscosity	: Dynamic: >1000 cP
Volatility (w/w)	: 0% (v/v). 0% (w/w).
VOC (W/W):	: 0 (g/l).

10. Stability and reactivity

Stable under recommended storage and handling conditions (see section 7).

Hazardous decomposition products: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

Keep away from the following materials to prevent strong exothermic reactions: OXIDIZING AGENTS, strong alkalis, strong acids.

11. Toxicological information

There is no data available on the preparation itself. The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and is classified for eco-toxicological properties accordingly. See Sections 2 and 15 for details. See Chapters 2 and 15 for details.

Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Solvents may cause some of the above effects by absorption through the skin. Symptoms and signs include headaches, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin. If splashed in the eyes, the liquid may cause irritation and reversible damage.

Based on the properties of the epoxy constituent(s) and considering toxicological data on similar preparations, this preparation may be a skin sensitizer and an irritant. It contains low-molecular epoxy constituents which are irritating to eyes, mucous membranes and skin. Repeated skin contact may lead to irritation and to sensitization, possibly with cross-sensitization to other epoxies. Skin contact with the preparation and exposure to spray mist and vapors should be avoided.

Based on the properties of epoxy constituent(s) and considering toxicological data on similar preparations, this preparation may be a skin sensitizer and a severe irritant. It contains epoxy-based reactive diluents which are moderately to severely irritating to eyes, mucous membranes and skin and are strong sensitizers. Repeated skin contact may lead to irritation and to hypersensitivity, possibly with cross-sensitization to other epoxies. Single oral exposure to doses of the epoxy-based reactive diluents at or close to the lethal dose has been shown to cause transient neurotoxic effects in animals in some cases. However, uptake through skin and by inhalation has not caused such effects in animals. Prolonged exposure to high concentrations may cause adverse effects in target organs such as the liver and kidneys.

Contains (Oxirane, mono [(C12-C16-alkyloxy)methyl] derivatives, Bisphenol-F-epoxy resin avg.mol.wght. < 700, Bisphenol-A-epoxy resin avg.mol.wght. < 700). May produce an allergic reaction.

Acute Data (LD₅₀, LC₅₀) - Toxicity to Test Animals

<u>Ingredient Name</u>	<u>Test</u>	<u>Result</u>	<u>Route</u>	<u>Species</u>
Bisphenol-A-epoxy resin avg.mol.wght. < 700	LD50	13600 mg/kg	Oral	Rat
	LD50	20000 mg/kg	Oral	Mouse
	LD50	>2000 mg/kg	Dermal	Rabbit
C12-C15 Alkyglycidylether	LD50	>10000 mg/kg	Oral	Rat

Local effects

Skin irritation	: Hazardous in case of skin contact (irritant).
Eye irritation	: Hazardous in case of eye contact (irritant).
Sensitization	: Hazardous in case of skin contact (sensitizer).
Chronic toxicity	: May cause sensitization by skin contact. The onset of symptoms may be delayed. May cause allergic skin reactions with repeated exposure.

5401 Impregnation Primer (Base)

Carcinogenic Effects : Not available.
Mutagenic Effects : Not available.

12. Ecological information

There is no data available on the preparation itself.
Do not allow to enter drains or watercourses.

The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and is classified for eco-toxicological properties accordingly. See Sections 2 and 15 for details.

Ecotoxicity Data

<u>Ingredient Name</u>	<u>Species</u>	<u>Period</u>	<u>Result</u>
Bisphenol-A-epoxy resin avg.mol.wght. < 700	fathead minnow Fathead minnow (pimephales promelas)	24 hours	3.1 mg/l
	zebra fish zebra fish (brachydanio rerio)	24 hours	9.4 mg/l
C12-C15 Alkylglycidylether	daphnia (EC50)	24 hours	1 mg/l
	Daphnia (EC50)	48 hours	1 to 10 mg/l

Mobility : Nonvolatile liquid.
Persistence/degradability : Non biodegradable according to OECD.

13. Disposal considerations

Do not allow to enter drains or watercourses.
Dispose of according to all federal, state and local applicable regulations.

Methods of disposal ; Waste of residues ; Contaminated packaging : Type: Hazardous chemical waste.
Location: European Union
Classification: H12 (Environmentally hazardous)
Disposal.: via incineration
Storage: * (Storage of controlled substances must comply with applicable regulatory security requirements. No specific storage is required. Use shelves or cabinets sturdy enough to bear the weight of the chemicals. Be sure that it is not necessary to strain to reach materials, and that shelves are not overloaded.)
Recycling: * (Not applicable.)

Waste Handling and Disposal : Avoid disposal, make attempts to use product completely in accordance with intended use. Dispose of this material and its container at hazardous or special waste collection points. Waste, used rags etc. should be collected, kept in a fireproof bin and destroyed in a safe way. Waste must be disposed of in accordance with federal, state and local environmental control regulations.

Waste Classification : Code: 080111 (08 01 11 waste paint and varnish containing organic solvents or other dangerous substances)
Classification: Y12 (Waste category according the Basel Convention)
Origin: * (Consult your local or regional authorities.)

European Waste Catalogue (EWC) : 080111



Hazardous Waste : This product is listed as Hazardous by the EU Directive on hazardous waste. Dispose of according to all federal, state and local applicable regulations.

14. Transport information

International transport regulations

Regulatory Information	UN number	Proper shipping name	Class	Packing Group	Label	Additional information
ADR/RID Class	3082	Environmentally hazardous substance, liquid, n.o.s. Limited Quantity	9	III		Hazard Identification Number 90 Limited Quantity LQ28 CEPIC Tremcard 90G01 Remarks Limited Quantity - ADR/IMDG 3.4.6
IMDG Class	3082	Environmentally hazardous substance, liquid, n.o.s. Limited Quantity	9	III		Emergency Schedules (EmS) F-A, S-F Remarks Limited Quantity - ADR/IMDG 3.4.6
IATA-DGR Class	3082	Environmentally hazardous substance, liquid, n.o.s. (epoxyresin)	9	III		Packaging Instruction 914

15. Regulatory information

EU Regulations	:	The product is labelled as follows, in accordance with local regulations:
Hazard symbol(s)	:	 
		Irritant, Dangerous for the environment
Risk Phrases	:	R36/38- Irritating to eyes and skin. R43- May cause sensitization by skin contact. R51/53- Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Safety Phrases	:	S25- Avoid contact with eyes. S26- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. S36/37- Wear suitable protective clothing and gloves. S61- Avoid release to the environment. Refer to special instructions/Safety data sheets. Contains epoxy constituents. See information supplied by the manufacturer. This information is provided by the current Safety Data Sheet.
Contains	:	C12-C15 Alkylglycidylether 271-846-8 Bisphenol-F-epoxy resin avg.mol.wght. < 700 500-006-8 Bisphenol-A-epoxy resin avg.mol.wght. < 700 500-033-5
Product Use	:	Classification and labeling have been performed according to EU directives 67/548/EEC, 1999/45/EC including amendments and the intended use. - Industrial applications.
Additional Warning Phrases	:	Contains epoxy constituents. See information supplied by the manufacturer. This information is provided by the current Safety Data Sheet.
EC Statistical Classification (Tariff Code)	:	3824 90 70

16. Other information

Full text of R-phrases appearing in section 2 : R36/38- Irritating to eyes and skin.
R43- May cause sensitization by skin contact.
R51/53- Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Designation of symbols in Section 2 : Xi - Irritant
N - Dangerous for the environment.

HISTORY

Date of printing : 27-6-2003. **Date of issue** : 18-6-2003.

Version : 1

Prepared by : RPM Europe - Department Environment, Health and Safety

Notice to Reader

This is an internet download copy, for information purposes only. The information in this sheet is believed to be in compliance with EU regulations, but neither Rust-Oleum nor any of its subsidiaries can guarantee it's full correctness. Any data contained herein may possibly not be up-to-date and specific national regulations apply in addition to the EU regulations. Up-to-date information and specific national editions are available upon request from our H&S dept. at fax nr. +31 165 593 600 or email address RPMEUROHAS@RUST-OLEUM.NL. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards may be described herein, we cannot guarantee that these are the only hazards that exist. RUST-OLEUM®, HARD HAT®, RUST-O-THANE®, RUST-O-CRYLIC® and COMBICOLOR 2=1® are registered trademarks of Rust-Oleum International Corporation, U.S.A. ©Copyright by Rust-Oleum Corporation, U.S.A.