

PEGACRYL

SATIN

TECHNICAL DATA SHEET

DATE : 07/01
ISSUE : 01
NUMBER : **TE-54**

► DESCRIPTION

Waterborne satin gloss acrylic paint.

► APPLICATION

Woodwork and walls both inside and outside.
As top coat on Noxyde.

► FEATURES

Excellent gloss retention at outdoor exposure – UV-resistant – good flow – good filling power – high covering capacity.

► TECHNICAL DATA

Binder	:	pure acrylic resins
Finish	:	satin gloss
Gloss (60°)	:	± 30
Colour (s)	:	white + colour chart
Solids content (ASTM, D1644/a)	:	in volume : 35 – 37 % in weight : 49 – 51 %
Density (ASTM, D1475, 20°C)	:	1.27 – 1.30 g/cm ³
VOC-content (Volatile Organic Compounds)	:	max. 160 g/l
Consumption	:	9 – 12 m ² /l per coat
Thickness wet film	:	100 micron (cons.: 10 m ² /l)
dry film	:	35 micron (cons.: 10 m ² /l)
Drying times	:	1 hour (10 m ² /l)
(for t° 20°C)	:	5 hours (10 m ² /l)
(for R.H. 60%)	:	24 hours
* dustfree	:	± 2 days
* rain resistant	:	
* recoatable	:	
* full cure	:	
Flashpoint (DIN53213)	:	not flammable

